

AI-ROT



Artificial Intelligence Optimization for
Production Lines Deploying Rotating
Machinery

Mechatronics Circus
Thursday 7th April 2022



Aalto University
School of Engineering



Overview of the consortium

Coordinator

Research partners



Industrial partners



International partners



Machine direction analysis

Rotating machine elements cause imperfections in the end product.

From measured end product quality variation:

- Separate repeating signals caused by rotating machine elements
- Order machine elements in order of significance (effect on end product quality)
- Obtain average pattern produced by single revolution of machine element

Measurement of end product






Image: Valmet




The punchline


Monitor the condition of multiple rolls based on a single measurement.




Video: Valmet QCS
<https://www.youtube.com/watch?v=XUKLIGlySp4>



I am to blame!
Repair me!!!




Patterns produced by rolls



| Source of error | Cause | Frequencies | Significance |
|-------------------------------------|--|--|--------------|
| Cross-section center-point movement | Unbalance , straightness error of the roll, movement caused by loads and bending stiffness variation, vertical component of end movements | ω 2ω (due to BSV) | High |
| Roundness errors | Roundness error due to manufacturing, wear, damages in the coating | $\omega, 2\omega, 3\omega \dots$ Harmonic series | Low / High |
| Movement of ends | Bearing geometry errors, flexing of the support structures, stochastic motion due to interplay between components | $\omega, 2\omega, 3\omega \dots$ Higher frequencies | Low |


Optimal filtering

MD variation (QCS data)




| Roll | Rotating frequency [Hz] |
|-------------|-------------------------|
| Former | 2.33 |
| 1.Press.up | 5.34 |
| 1.Press.low | 4.67 |
| 2.Press.up | 6.75 |
| 2.Press.low | 1.21 |
| 1.Dry | 3.49 |
| ... | ... |

- Method for extracting repeating patterns from noisy data
- Filter function is created considering harmonic signal model with noise, not just multiples of frequencies [1]




1. Separate repeating patterns
2. Identify components causing most variation


Preliminary results – artificial data




Preliminary results – real data



Application

| Roll | Rotating frequency [Hz] | Pattern RMS power | Pattern | Harmonics |
|----------|-------------------------|-------------------|---|--|
| Thermo | 2.54 | 4.5 |  |  1 2 3 4 5 |
| Press up | 5.34 | 3.5 |  |  1 2 3 4 5 |
| Caland1 | 2.12 | 3.4 |  |  1 2 3 4 5 |
| Spreader | 5.10 | 2.8 |  |  1 2 3 4 5 |
| Caland2 | 4.65 | 2.7 |  |  1 2 3 4 5 |



Component effects over time




Conclusions

Develop tools for machine direction data analysis.

Monitor the condition of multiple rolls based on a single measurement at end of process.



I am to blame!
Repair me!!!



Contact



Tuomas Tiainen

Postdoctoral researcher
tuomas.tiainen@aalto.fi



Raine Viitala

Assistant professor
raine.viitala@aalto.fi